

SVT



Amplifier Front Panel:

Channel 1: Bright and Normal input jacks, Volume, Treble, Bass, Selective Midrange cut or boost, Ultra Hi, 3-way Ultra Lo and Midrange Frequency Select.

Channel 2: Bright and Normal input jacks, Volume, Treble, Bass, Ultra Hi and Ultra Lo. Power on-off, Polarity switch and indicator light.

Amplifier Rear Panel:

Standby switch, fuse post, speaker jack, (4 ohm) extension speaker jack, (4 ohm) and extension amplifier jack for tandem operation or recording.

SVT Speaker System:

Each SVT speaker enclosure has 8-10" speakers in 4 separate compartments. A total of sixteen speakers in two enclosures.

Amplifier Performance:

300 watts RMS (over 700 watts peak music power.)

Amplifier Tube and Diode Complement:

6-6146B/8298A's, 3-12DW7's, 2-12BH7's, 2-12AX7's, 1-6C4, 12 silicon diodes.

Amplifier Dimension and Shipping Weights:

Amplifier Cabinet:

23½" wide, 14" deep, 11" tall.
Shipping Weight — 85 pounds.

Speaker Cabinets:

25½" wide, 16" deep, 48" tall.
Shipping weight — (2) 210 pounds.
Covers optional.

The Ampeg SVT was designed for the musician who needs concert hall levels of sound and power with consistent quality and reliability. The SVT offers unheard of power in a tube amplifier, coupled with a unique speaker complement. Big and brawny, the SVT must be seen and heard to be believed!



THE AMPEG COMPANY, INC.
330 DALZIEL ROAD
LINDEN, NEW JERSEY 07036